

# F76 Plus FILM DEVELOPER

## *Fine Grain Developer*

**F76 Plus FILM DEVELOPER** is a long lasting phenidone-based developer, and relatively safer to use. Performs well with all films and especially with Kodak T-MAX films.

**F76 Plus FILM DEVELOPER** is an extremely fine grain, variable dilution (contrast) developer with excellent latitude for control. Increase concentration to increase contrast, dilute to decrease contrast. **F76 Plus FILM DEVELOPER** can be diluted to 1+19 for push processing. Normal range of dilution is 1+3 to 1+14.

**F76 Plus FILM DEVELOPER** is ideal for automatic machine processing, replenished with working solution, prepared by diluting concentrate 1+4 to 1+5, at the rate of 0.4 ml/sq.in. film.

### Suggested starting points for film developing times:

	68°F @ 1+9 Normal Dev.	75°F @ 1+9 Normal Dev.	75°F @ 1+19 Pushed Dev.
Kodak T-MAX 100	7 min	6 min	12 min
Kodak T-MAX 400	8 min	7 min	12½ min
Kodak TRI-X Pan	6 min	5½ min	11 min
Kodak PLUS-X Pan	5½ min	5 min	9 min
Agfapan APX 100	9 min	6½ min	12½ min
Agfapan APX 400	8 min	6 min	12 min
Ilford FP4	5½ min	5 min	9 min
Ilford HP5	7 min	6 min	12 min
Fuji Neopan 400	6 min	5½ min	11 min

### CATALOG NUMBER

**11 0714****11 0717****11 0728**

### PACKAGE

**12x 32 ounces****4x 1 Gallon****5 Gallons**